

MOWER REAPER-BINDER 622

TECHNICAL FEATURES

| | |
|---------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------|
| MOTOR | Lombardini 3LD450 |
| Power Supply | Diesel |
| Starter | Recoil |
| Power CV/KW | 10 / 7,5 |
| GEARBOX | |
| Type | Gears in oil bath |
| No. of gears | 4+1 |
| Forward speed in km/h | I: 5,5 - II: 7,5 - III: 10 - IV: 14,2 - RM: 6 |
| CLUTCH | Dry, mono disc with manual control |
| BRAKES | Independently controlled on the two wheels, they are of a special type housed in the reduction gear on the deck |
| STEERING SYSTEM | Differential with lock |
| POWER TAKE-OFF | Independent at 1125 rpm |
| WHEELS | 4.50 - 19 |
| SAFETY DEVICES | In compliance with EC standards |
| WEIGHT Tractor unit with engine without attachments kg | 195 |
| MAIN EQUIPMENT | |
| Cutter bar | Working width cm: 127 or 140 with traditional low cut or middle cut fingers |
| Standard reaper binder | Working width cm.140 – binding height cm. 28 height of crop to be harvested from 35 to 70/80 cm. |
| Special reaper binder | Working width cm.140 binding height cm. 28 height of crop to be harvested from 35 to 160 cm. |
| Work and travel sulky | Normal with two tubes for grass – Special single-tube for applications on reaper-binders |
| WEIGHT cutter bar kg | 80 |
| WEIGHT Standard reaper binder kg | 200 |
| WEIGHT Special Reaper binder kg | 240 |
| WEIGHT Work and travel sulky kg | 45 |

