

# TECHNICAL FEATURES

	Engine	Fuel	Starter	Power kW/HP	Gearbox	Speeds FWD/REV	Quick reverser	Clutch	Brakes	Differential	PTO	Handlebars	Wheels	Safety devices
<b>728</b> PowerSafe®	HONDA GP160	Gasoline	Recoil	3,6 / 4,8	With gears and worm screw in oil bath	3 + 3	Yes	PowerSafe®, hydraulic with manual control	Parking brake	No	Independent from gearbox. At 990 rpm (with engine at 3600 rpm) with engagement in oil bath	Mounted on silent-blocks, adjustable in height and sideways and reversible	4.00-8 4.0-10 6.5/80-12 Steel cage wheels Ø 43 cm	In compliance with the EN 709/A4 regulation
	HONDA GX200	Gasoline	Recoil	4,1 / 5,5										
	HONDA GX270	Gasoline	Recoil	6,3 / 8,4										
	BRIGGS&STRATTON XR1450	Gasoline	Recoil	7 / 9,5										
	KOHLER KD350	Diesel	Recoil	5,5 / 7,5										
<b>738</b> PowerSafe®	HONDA GX270	Gasoline	Recoil or electric	6,3 / 8,4	With gears and worm screw in oil bath	3 + 3	Yes	PowerSafe®, hydraulic with manual control	Parking brake on the two wheels	With lock	Independent from gearbox. At 990 rpm (with engine at 3600 rpm) with engagement in oil bath	Mounted on silent-blocks, adjustable in height and sideways and reversible	5.0-10 6.5/80-12 Steel cage wheels Ø 43 cm	In compliance with the EN 709/A4 regulation
	HONDA GX340	Gasoline	Recoil	8 / 10,7										
	BRIGGS&STRATTON XR1450	Gasoline	Recoil	7 / 9,5										
	KOHLER KD350	Diesel	Recoil or electric	5,5 / 7,5										
<b>740</b> PowerSafe®	HONDA GX390	Gasoline	Recoil or electric	8,7 / 11,7	With gears and worm screw in oil bath	3 + 3	Yes	PowerSafe®, hydraulic with manual control	Independent work brake on the two wheels and parking brake	With lock	Independent from gearbox. At 990 rpm (with engine at 3600 rpm) with engagement in oil bath	Mounted on silent-blocks, adjustable in height and sideways and reversible	5.0-10 6.5/80-12 Steel cage wheels Ø 49 cm	In compliance with the EN 709/A4 regulation
	BRIGGS&STRATTON XR2100	Gasoline	Recoil	8,5 / 11,4										
	YANMAR LN100	Diesel	Recoil or electric	7,5 / 10										
<b>750</b> PowerSafe®	HONDA GX390	Gasoline	Recoil	8,7 / 11,7	With gears and worm screw in oil bath	3 + 3	Yes	PowerSafe®, hydraulic with manual control	Independent work brake on the two wheels and parking brake	With lock	Independent from gearbox. At 990 rpm (with engine at 3600 rpm) or 825 rpm (with 3LD510 engine at 3000 rpm) with engagement in oil bath	Mounted on silent-blocks, adjustable in height and sideways and reversible	6.5/80-12 Steel cage wheels Ø 58 cm	In compliance with the EN 709/A4 regulation
	KOHLER KD440	Diesel	Recoil or electric	8 / 10,9										
	LOMBARDINI 3LD510	Diesel	Recoil or electric	9 / 12,2										
<b>770<sup>HY</sup></b> PowerSafe®	HONDA GX390	Gasoline	Recoil or electric	8,7 / 11,7	With gears and worm screw in oil bath	2-speed ranges (slow/fast) in both FWD and REV	By hydrostatic unit	PowerSafe®, hydraulic with manual control	Independent work brake on the two wheels and parking brake	With lock	Independent from gearbox. At 990 rpm (with engine at 3600 rpm) with engagement in oil bath	Mounted on silent-blocks, adjustable in height and sideways and reversible	5.0-10 6.5/80-12 Steel cage wheels Ø 49 cm	In compliance with the EN 709/A4 regulation
	BRIGGS&STRATTON XR2100	Gasoline	Recoil	8,5 / 11,4										
	YANMAR LN100	Diesel	Recoil or electric	7,5 / 10										