

# ROTEX XT

## Rear mounted disc mowers

TECHNICAL FEATURES	ROTEX XT 5	ROTEX XT 6	ROTEX XT 7
Number of discs	5	6	7
Cutting width (mm)	2050	2450	2850
Min./max. swath width (mm)	650 / 1050	1050 / 1450	1450 / 1850
Weight (kg)	560	600	645
PTO power (kW/hp)	25 / 34	30 / 41	35 / 48
Adjustable frame with linkage categories 1 and 2	standard outfit		
Tractor PTO rotation speed	540 rpm		
Nodular cast iron control support	standard outfit		
Transmission	with gears in oil bath		
Disc rotation	normal or counter-rotating		
Discs with knife quick release	optional		
Disc holding flanges with torque limiter	standard outfit		
Conveying cones	standard outfit, on the first and last disc		
Adjustable swath boards	standard outfit, with one external swathing wheel		
Wear slides in special boron/manganese steel	standard outfit		
Baffles in blade overlap zone	standard outfit		
Safety release with bar retraction in case of impacts against obstacles	standard outfit		
Bar balancing by lightening springs and tie-rods	standard outfit		
Bar protection	canvas type, with impact-preventing plastic shields		
Hydraulic lifting of the shearbar	standard outfit		
Hydraulic remote control valves of the tractor	1 single-acting		
Bar sloping	from +90° (transport position) to -35° vs. the horizontal plane		
Cardan shaft with free release	standard outfit		