

# ROTEX XR

## Rear mounted mower-conditioners

TECHNICAL FEATURES	ROTEX XR 5	ROTEX XR 6	ROTEX XR 7
Number of discs	5	6	7
Cutting width (mm)	2050	2450	2850
Min./max. swath width (mm)	760/1180	1160/1580	1070/1630
Weight (kg)	720	780	900
PTO power (kW/hp)	40 / 54	50 / 68	55 / 75
Adjustable frame with linkage categories 1 and 2	standard outfit		
Tractor PTO rotation speed	540 rpm		
Nodular cast iron control support	standard outfit		
Transmission	with gears in oil bath		
Disc rotation	standard		
Disc holding flanges with torque limiter	standard outfit		
Conveying cones	standard outfit, on the first and last disc		
Adjustable swath boards	standard outfit		
Wear slides in special boron/manganese steel	standard outfit		
Baffles in blade overlap zone	standard outfit		
Safety release with bar retraction in case of impacts against obstacles	standard outfit		
Bar balancing by lightening springs and tie-rods	standard outfit		
Bar protection	canvas-type with plastic shock-resistant plastic shield at the front and steel with upper baffle for forage flow control at the back		
Hydraulic lifting of the shearbar	standard outfit		
Hydraulic remote control valves of the tractor	1 single-acting		
Bar sloping	from +90° (transport position) to -35° vs. the horizontal plane		
Cardan shaft with free release	standard outfit		
Conditioner with upper swinging roller for foreign body ejection	special polyurethane resin roller type with chevron ribs		
Lower roller protection	standard outfit		
Adjustment of conditioning pressure by lever control	standard outfit		
Roller clearance adjustment	from 0 to 40 mm		
Roller rotation speed (with PTO at 540 rpm)	1300 rpm		
Conditioning width (mm)	1400	1800	2200