



TECHNICAL FEATURES	ROTEX 5 AVANT NT	ROTEX 6 AVANT NT	ROTEX 7 AVANT NT
"Standard" hitch with couplings cat. 1 and 2	at your choice	at your choice	at your choice
"Standard" hitch with couplings cat. 1 and 2 for isodiametric tractors	at your choice	at your choice	at your choice
"Accord" hitch	at your choice	at your choice	at your choice
Hydraulic displacement	optional	optional	optional
Number of discs	5	6	7
Cutting width (mm)	2050	2450	2850
Max. width in working condition (mm)	2920	3320	3720
Max. width in transport condition (mm)	2050	2450	2850
Transmission designed both for right and left-hand turning PTO tractors	standard	standard	standard
Cast-iron control support	standard	standard	standard
Transmission with gears in oil bath	standard	standard	standard
Free wheel and clutch to protect the transmission	standard	standard	standard
Disc-holding flanges fixed on the bar for an easy inspection and maintenance	standard	standard	standard
Disc holding flanges with torque limiter	standard	standard	standard
Wear-resistant skids	standard	standard	standard
Baffles in blade overlap zone	standard	standard	standard
Bar balancing by springs	standard	standard	standard
Swath width (mm)	850 / 910	1200 / 1350	1250 / 1500
Indicative weight of the machine with "Standard" hitch without displacement (kg)	540	590	640
PTO power (kW/HP)	30 / 40	35 / 48	40 / 54