



ROTEX AVANT NT

TECHNICAL FEATURES	ROTEX R6 AVANT NT	ROTEX R7 AVANT NT
"Standard" hitch with couplings cat. 1 and 2	at your choice	at your choice
"Standard" hitch with couplings cat. 1 and 2 for isodiametric tractors	at your choice	at your choice
"Accord" hitch	at your choice	at your choice
Hydraulic displacement	optional	optional
Number of discs	6	7
Cutting width (mm)	2450	2850
Max. width in working condition (mm)	3320	3720
Max. width in transport condition (mm)	2450	2850
Chevrons roller conditioner, width 1800 mm (R6) e 2100 mm (R7), with adjustable pressure through torsion bar and external lever	standard	standard
Transmission designed both for right and left-hand turning PTO tractors	standard	standard
Cast-iron control support	standard	standard
Transmission with gears in oil bath	standard	standard
Free wheel and clutch to protect the transmission	standard	standard
Disc-holding flanges fixed on the bar for an easy inspection and maintenance	standard	standard
Disc holding flanges with torque limiter	standard	standard
Wear-resistant skids	standard	standard
Baffles in blade overlap zone	standard	standard
Bar balancing by springs	standard	standard
Swath width (mm)	1200 / 1350	1250 / 1500
Indicative weight of the machine with "Standard" hitch without displacement (kg)	760	830
PTO power (kW/HP)	50 / 68	55 / 75